

General Purpose Relays

841



Features:

- Heavy duty 30A 240VAC, 25A 240VAC power type
- AC & DC coils are both available
- PCB terminals and quick terminal types
- Optional for special large contact gap 3.0mm version
- Complies with RoHS-Directive 2011/65/EU

Applications:

- Automotive, Industrial

731



Features:

- 10A general purpose Power Relay
- SPDT, DPDT, TPDT contact configurations
- AC & DC coils are both available
- Optional for anti-rotation tab, tapped core, indicator lamp
- Complies with RoHS-Directive 2011/65/EU

Applications:

- Home appliances

507 / 881



Features:

- High rating miniature PCB Relay
- AC & DC coil are both available
- 17A 277VAC, inrush rating application is available
- High temperature withstand up to 125°C

Applications:

- Industrial

202 / 835 / 812



Features:

- Miniature 12A 125VAC PCB Relay
- 450mW and 20mW coil are available
- High CTI 250 material
- UL Insulation Class F
- Optional for halogen free version

Applications:

- Motor Control, Compressor Control

Contact:

IBH Elektrotechnik GmbH
Gutenbergring 35
22848 Norderstedt
GERMANY

Beate Heidorn
Tel.: +49 40 523052-26
Fax: +49 40 5239709

bheidorn@ibh-elektrotechnik.de
www.ibh-elektrotechnik.de

No responsibility is taken for the correctness of this information. See technical data of the manufacturer.



Automotive Relays

409



Features:

- 200A high power automotive Relay
- SPNO contact configuration
- Switches up to 200A resistive load, 50.000 ops., 23°C
- Optional resistor or diode for coil transient suppression
- Complies with RoHS-Directive 2011/65/EU and ELV-Directive 2000/53/EC

Applications:

- Alternative Energy

301 / 871



Features:

- Micro 280 automotive Relay
- NO contacts switch 35A resistive load
- Micro ISO automotive Relay
- NO contacts switch 35A resistive load
- SPNO / 3 Terminals relay of cos saving version

Applications:

- Automotive, Building Equipment / Lighting

832 / 822



Features:

- Heavy duty 20/30A automotive PCB Relay
- High dielectric strength up to 4000Vrms
- High power PCB Relay with 40A rating
- USA & European footprint are both available
- Open frame, dust cover, flux-free type and sealed are available

Applications:

- Communication

102 / 896 / 897



Features:

- High rating 20A with max. switching current up to 30A
- NO contacts switch 50A resistive load, NC contacts switch 30A resistive load
- Switches up to 70A resistive load, High Power Mini ISO Relay

Applications:

- Industrial, Alternative Power Vehicle

Contact:

IBH Elektrotechnik GmbH
Gutenbergring 35
22848 Norderstedt
GERMANY

Beate Heidorn
Tel.: +49 40 523052-26
Fax: +49 40 5239709

bheidorn@ibh-elektrotechnik.de
www.ibh-elektrotechnik.de

No responsibility is taken for the correctness of this information. See technical data of the manufacturer.

