

















Relays Selection Chart



Type		305	205	888	888 (inrush)
Photo					
	Description				
Outline (L×W×H) mm No including terminals		27.5×21×37.4	37×35.5×59	29×12.7×15.7	29×12.7×15.7
Contact configuration		2C、4C	2C、3C、2T、3T	1A、1B、1C	1A、1C
Max. Allowable Contact current (A)	45				
	40				
	35				
	30				
	25				
	20				
	15				
	10				
5					
3					
Contact rating Resistive load		10A 250VAC	2C/3C : 10A 250VAC 2T/3T : 4A 250VAC	12A 240VAC (888/N) 10A 240VAC (N1) 16A 240VAC(H/HN)	1500W 240VAC
Coil voltage	DC	12 ~ 220V	12~220V	3~48V	3~48V
	AC	12 ~ 240V	24~230V	6~240V	-----
Power consumption	DC	1.0W	1.2W	0.53W、0.40W、0.25W	0.53W
	AC	0.98VA	2.0VA	0.75VA	-----
Life expectancy	Mechanical (Min.)	2×10 ⁷	2×10 ⁷	3×10 ⁷	3×10 ⁷
	Electrical (Min.)	-----	-----	1×10 ⁵	3×10 ⁴
Dielectric strength	Open contact	1000VAC	1500VAC	1000VAC	1000VAC
	Contact and coil	2500VAC	2500VAC	5000VAC	5000VAC
	Contact circuits	2000VAC	2500VAC	-----	-----
Terminal layout					
mm (inch)					
Bottom view (PCB layout)					
Terminal type					
Safety approval		UL CSA	UL CSA	UL VDE	UL VDE
Page no.		6-10	11-17	18-30	18-30

IBH ELEKTROTECHNIK GMBH
Postfach 32 09, 22825 Norderstedt
Gutenbergring 35, 22848 Norderstedt



Hamburg
Osnabrück
Rendsburg
IBH

Elektronik (0 40) 52 30 52 21-22
Elektromechanik (0 40) 52 30 52 26
Zentrale (0 40) 52 30 52-0
Telefax (0 40) 52 88 21 63
e-Mail info@IBH-Elektrotechnik.de



Relays Selection Chart

882	735	841
28×5×15	38×34.8×47.5	51.5×34.9×36.8
1A、1C	1 form C to 3 form C	1 form A、2 form A
NC : 6A 240VAC NO : 8A 240VAC NC/NO : 6A/6A 240VAC	1,2 form C 20A 240VAC 3 form C 20A 120VAC	1A : 30A 220VAC 2A : 25A 220VAC
3~60V	6~125V	3~200V
-----	6~240V	6~240V
0.21W、0.17W	1.2W、1.5W	1.92W
-----	3.0VA、3.4VA	1.7VA~2.7VA
1×10 ⁷	1×10 ⁷	5×10 ⁶
1×10 ⁴	1×10 ⁵	1×10 ⁵
1000VAC	1000VAC	2000VAC
4000VAC	1600VAC	4000VAC
-----	1600VAC	2000VAC
UL VDE	UL CSA FI/CE	UL TUV
31-36	37-43	44-50

IBH ELEKTROTECHNIK GMBH
Postfach 32 09, 22825 Norderstedt
Gutenbergberg 35, 22848 Norderstedt



Elektronik (0 40) 52 30 52 21-22
Elektromechanik (0 40) 52 30 52 26
Zentrale (0 40) 52 30 52-0
Telefax (0 40) 52 88 21 63
e-Mail info@IBH-Elektrotechnik.de